



3p. Cat II





# Serie 220.350

HP 120/350 - KW 88/257  
15/50 cm. - 6/20 inc.



3012

Mod.	cm.	inc.	HP min./max.	KW min./max.	N.	kg.	Lbs.
G 2508	245	96	120/350	88/257	8	2880	6336
G 2510	245	96	120/350	88/257	10	3050	6710
G 3010	300	118	130/350	95/257	10	3250	7150
G 3012	300	118	140/350	102/257	12	3400	7480
G 3512	350	138	160/350	118/257	12	3580	7876
G 3514	350	138	160/350	118/257	14	3750	8250
G 4016	400	157	180/350	132/257	16	4110	9042
G 4516	450	177	200/350	147/257	16	4340	9548



**— Distanza fra le vanghe.**

Average clearance between spades.

Distance moyenne entre les bêches.

Distancia entre las azadas.

Durchschnittlicher Abstand zwischen den Spaten.



Mod.	cm	inch.	Mod.	cm	inch.
804	20	8	2008	25	10
904	22,5	9	2208	27,5	11
1004	25	10	2508	30,6	12
1104	27,5	11	2210	22	8 1/2
1154	28,7	11 1/2	2510	24,5	9 1/2
1206	20	8	2710	27	10 1/2
1306	21,7	8 1/2	3010	30	12
1456	24,2	9 1/2	3012	25	10
1506	25	10	3512	29,2	11 1/2
1606	26,7	10 1/2	3514	25	10
1656	27,5	11	4016	25	10
1808	22,5	9	4516	28,1	11