

SERIE 220.350

HP 120/350 - KW 88/257

15/50 cm - 6/20 in

3p. Cat II



OPTIONAL

3012

Mod.	cm	in	HP min / max	KW min / max	N. 	kg	Lb
G 2508	245	96	120/350	88/257	8	2880	6336
G 2510	245	96	120/350	88/257	10	3050	6710
G 3010	300	118	130/350	95/257	10	3250	7150
G 3012	300	118	140/350	102/257	12	3400	7480
G 3512	350	138	160/350	118/257	12	3580	7876
G 3514	350	138	160/350	118/257	14	3750	8250
G 4016	400	157	180/350	132/257	16	4110	9042
G 4516	450	177	200/350	147/257	16	4340	9548



2 / 3,5 Km/h

1,2 / 2,2 miles/h





— Distanza fra le vanghe.

Average distance between spades.

Distance moyenne entre les bêches.

Distancia entre las azadas.

Durchschnittlicher Abstand zwischen den Spaten.



Mod.	cm	in
804	20	8
904	22,5	9
1004	25	10
1104	27,5	11
1154	28,7	11 1/2
1206	20	8
1306	21,7	8 1/2
1456	24,2	9 1/2
1506	25	10
1606	26,7	10 1/2
1656	27,5	11
1808	22,5	9

Mod.	cm	in
2008	25	10
2208	27,5	11
2508	30,6	12
2210	22	8 1/2
2510	24,5	9 1/2
2710	27	10 1/2
3010	30	12
3012	25	10
3512	29,2	11 1/2
3514	25	10
4016	25	10
4516	28,1	11