

BIVANGA® Serie 150.150

HP 50/150 - KW 36/110

10/65 cm. - 4/26 inc.

3p. Cat II



2510

Mod.	cm. \longleftrightarrow inc.	HP min./max.	KW min./max.	N. \updownarrow	kg.	Lbs.
B 1506 P	150 59	50/150	36/110	12	1190	2618
B 1656 P	165 65	50/150	36/110	12	1220	2684
B 1808 P	180 71	55/150	40/110	16	1470	3234
B 2008 P	200 79	60/150	44/110	16	1490	3278
B 2208 P	220 87	65/150	47/110	16	1540	3388
B 2510 P	245 96	80/150	58/110	20	1790	3938



p.18-19



PdF. 540= I 145 II 167 III 205 RpM

PdF. 1000= I 140 II 163 III 205 RpM

RUOTE BOMBATE - Curved wheels - Roues bombées - Ruedas combadas - Gewölbte Räder

x Serie	\emptyset x \longleftrightarrow inc.
	cm. inc..
150.150/200 180 B 160	50x19 20x7 1/2
150.150/200 180 B 160	50x25 20x10
150.150/200 180 B 160	50x31 20x12 1/4
220	50x19 20x7
220	50x25 20x10
220	50x31 20x12 1/4

RUOTE A SPERONI - Stake wheels - Roues à dents - Ruedas a espolones - Gespornte Räder

x Serie	\emptyset x \longleftrightarrow inc.
	cm. inc.
150.150/200 180 B 160	40x40 16x16
150.150/200 180 B 160	45x50 18x20
220	40x40 16x16
220	45x50 18x20