


# SERIE 150.150

HP 50/150 - KW 36/110

10/65 cm - 4/26 in



3p. Cat II

OPTIONAL



2510

Mod.	cm	↔	in	HP min / max	KW min / max	N. ☐	kg	Lb
B 1506 P	150		59	50/150	36/110	12	1190	2618
B 1656 P	165		65	50/150	36/110	12	1220	2684
B 1808 P	180		71	55/150	40/110	16	1470	3234
B 2008 P	200		79	60/150	44/110	16	1490	3278
B 2208 P	220		87	65/150	47/110	16	1540	3388
B 2510 P	245		96	80/150	58/110	20	1790	3938



p.18-19



PdF 540= I 145 II 167 III 205 RpM

PdF 1000= I 140 II 163 III 205 RpM

## RUOTE BOMBATE - Curved wheels - Roues bombées Ruedas abombadas - Gewölbte Räder

x Serie

∅ x ↔

cm

in

150.150/200 180 B 160

50x19

20x7 1/2

150.150/200 180 B 160

50x25

20x10

150.150/200 180 B 160

50x31

20x12 1/4

220

50x19

20x7

220


50x25

20x10

220

50x31

20x12 1/4



## RUOTE A SPERONI - Stake wheels - Roues à dents Ruedas a espolones - Gespornte Räder

x Serie

∅ x ↔

cm

in

150.150/200 180 B 160

40x40

16x16

150.150/200 180 B 160

45x50

18x20

220

40x40

16x16

220

45x50

18x20

